



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

## TRANS EXTREM 75W

**100% synthetic lubricant for transmissions**

### DESCRIPTION

GRO Gear extrem 75 W is a 100% synthetic valve designed for high competition in the most extreme conditions of wear and high temperature. Its great lubricating ability, its EP properties and film resistance translate into less friction, less wear and lower temperature. This means more efficient power transmission and longer life.

### PERFORMANCE

**STANDARDS:** API GL-5

**RECOMMENDATIONS:** VERTIGO  
HONDA  
RIEJU

GRO Gear extrem 75 W has been developed with the best competition specialists using the most advanced technologies to achieve perfect lubrication in the most extreme conditions. It is also highly compatible with all the polymers used in engine O-rings, preventing their deformation.

### CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

### TECHNICAL FEATURES

<b>SAE VISCOSITY:</b>	75W	<b>FREEZING POINT:</b>	-50°C / -58 F
<b>VISCOSITY AT 100°C:</b>	5.2 mm <sup>2</sup> /s	<b>FLASHPOINT:</b>	215°C / 419 F
<b>VISCOSITY AT 40°C:</b>	20 mm <sup>2</sup> /s		
<b>VISCOSITY INDEX:</b>	212		

Rev. 11/23



[www.globalracingoil.com](http://www.globalracingoil.com)

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.



INNOVATIVE SME  
Subvenció per 2016-2019

