



**ON-E**  
K I D S

**20"**

**TECHNICAL DATA**

**TRRS ON-E KIDS**

**2025**

<b>CHASIS / FRAME</b>	Fundición de aluminio / Aluminium die casting
<b>BASCULANTE / SWINGARM</b>	Fundición de aluminio / Aluminium die casting
<b>LONGITUD MÁXIMA / MAX. LENGTH</b>	1600 mm
<b>DIST. ENTRE EJES / DIST. BETWEEN AXIS</b>	1050 mm
<b>ANCHO MÁXIMO / MAX. WIDTH</b>	687 mm
<b>ALTURA MÁXIMA / MAX. HEIGHT</b>	990 mm
<b>ALTURA ASIENTO / SEAT HEIGHT</b>	560 mm
<b>DIST. MÍNIMA AL SUELO / GROUND CLERANCE</b>	280 mm
<b>ALTURA ESTRIBOS/ FOOTREST HEIGHT</b>	320 mm
<b>SUSPENSIÓN DEL. / FRONT SUSPENSION</b>	26" regulables // 100 mm Carrera / Travel // Barras / Bars Ø32 mm aluminio/aluminum
<b>AMORTIGUADOR TRAS. / REAR SHOCK</b>	Hidráulico / Hidraulic. Ajustable en rebote y precarga muelle
<b>RECORR. RUEDA TRAS. / TRAVEL REAR WHEEL</b>	90mm / Sistema de bieletas progresivas TRRS / Progressive linkage system TRRS
<b>PESO / WEIGHT</b>	27 Kg
<b>FRENO DELANTERO / FRONT BRAKES</b>	Hidráulicos / Hydraulic Ø160 mm
<b>FRENO TRASER / REAR BRAKES</b>	Hidráulicos / Hydraulic Ø160 mm
<b>RUEDA DELANTERA / FRONT TYRE</b>	Rebel XBIKE trial 20x2.5
<b>RUEDA TRASERA / REAR TYRE</b>	Rebel XBIKE trial 20x3.0
<b>MOTOR</b>	1350W 48V
<b>BATERÍA / BATTERY</b>	Ion litio / Lithium-ion 48V (17,5Ah)
<b>AUTONOMÍA USO / OPERATING TIME</b>	Hasta / Until 3h
<b>CARGADOR / CHARGING</b>	Cargador litio / Lithium charger: AC90V-260V DC 54.6V 5A
<b>TIEMPO DE CARGA / CHARGE TIME</b>	Máximo / Up to: 3.5h
<b>CORONA TRASERA / REAR SPROCKET</b>	Aluminio / Aluminium 86z
<b>CONTROLADORA / CONTROLLER</b>	Programable velocidad, potencia, respuesta - Adjustable speed, power, response